

Compressed Air Technologies



TA-120/15HP.



TA-100/10HP.



TA-100/7.5HP.



TA-80/5.5HP.



TA-65/2HP.



VA-65/1HP.

SPECIFICATIONS

Belt - Drive Single Stage

MODEL	HP - KW	Bore Stroke	AIR ℓ/min	NO.	WORK $\text{Kg}/\text{cm}^2/\text{psi}$	MAX $\text{Kg}/\text{cm}^2/\text{psi}$	R.P.M.	AIR ℓ/Liter	CM
VA-65	1 0.75	65 44	205	2	8 116	10 145	635	90	Ø 350 x 980
TA-65	2 1.5	65 48	310	3	8 116	10 145	635	150	Ø 400 x 1000
VA-80A	3 2.2	80 60	560	2	8 116	10 145	770	165	Ø 400 x 1130
VA-80B	3 2.2	80 60	560	2	8 116	10 145	770	260	Ø 500 x 1100
TA-80A	5.5 4.0	80 60	900	3	8 116	10 145	900	260	Ø 500 x 1100
TA-80B	5.5 4.0	80 60	900	3	8 116	10 145	900	315	Ø 500 x 1400
VA-100	7.5 5.5	100 70	1290	2	8 116	10 145	970	315	Ø 500 x 1400
TA-100	10 7.5	100 70	1790	3	8 116	10 145	970	315	Ø 500 x 1400
TA-120	15 11	120 80	2850	3	8 116	10 145	860	520	Ø 600 x 1510

SPECIFICATIONS

Belt - Drive Two Stage

MODEL	HP - KW	Bore Stroke	AIR ℓ/min	NO.	WORK $\text{Kg}/\text{cm}^2/\text{psi}$	MAX $\text{Kg}/\text{cm}^2/\text{psi}$	R.P.M.	AIR ℓ/Liter	CM
HVA-65	1 0.75	65 x44,42 x44	120	2	12 175	15 218	750	90	Ø 350 x 980
HTA-65	2 1.5	65 x48,51 x48	260	3	12 175	15 218	800	150	Ø 400 x 1000
HTA-80H	3 2.2	65 x48,51 x48	350	3	12 175	15 218	990	165	Ø 400 x 1130
HTA-80A	5.5 4.0	80 x60,65 x60	655	3	12 175	15 218	950	260	Ø 500 x 1100
HTA-100	7.5 5.5	100 x70,80 x70	825	3	12 175	15 218	800	315	Ø 500 x 1400
HTA-100H	10 7.5	100 x70,80 x70	1255	3	12 175	15 218	990	315	Ø 500 x 1400
HTA-120	15 11	120 x80,100 x80	1820	3	12 175	15 218	860	520	Ø 600 x 1510